

**T** *SERIES*  
**MAJOR**

**TN 5800**



# AC TRACTORS

Inspired by Mediterranean agriculture, **TN 5800** is the equal-wheeled steering wheel of the **Major series** (51.5 HP Yanmar engine), suitable for professional use. A tractor at ease even on steep slopes, which offers all the grip, maneuverability and compactness needed on steep and uneven terrain.

**TN Major** aims to give maximum comfort to the operator: the handles on the rear mudguards, useful when working on slopes, also aid access to a large, unobstructed driving position, welcoming for operators of any size.

ANTONIOCARRARO.COM



N°1 SPECIAL TRACTORS

# TECHNICAL DATA: TN 5800

<b>Frame</b>	ACTIO™ integral oscillating frame • Unidirectional • Steering wheels • 4 equal-size driving wheels • Rear final drives	
<b>Engine type</b>	Supercharged diesel with common rail direct injection Emissions Standard: <b>Stage 5</b> N° Cylinders: 4 - 16 Valves Rated rpm: 2600 Tank capacity (litres): 38.5	Power kW/CV (97/68/CE): 37.9/ 51,5  Max torque (Nm/rev): 168,2/1690
<b>Transmission</b>	24 speed synchronised gearbox: 12 FWD + 12 REV with shuttle	
<b>PTO</b>	Independent, mechanical control, standard 540 rpm and synchronised groundspeed	
<b>Shaft</b>	1 3/8" splined	
<b>Rear linkage</b>	Rear hydraulic lift with 3-point linkage Lifting capacity (kg): 2200 Oscillating lift arms and lateral stabilizer bars, Cat. 1; Category "C" adjustable rear tow hook	
<b>Steering</b>	Hydraulic 2 pistons	
<b>Brakes</b>	Service: rear oil-immersed disc brakes with mechanical control, steering brakes - Emergency and parking brakes acting on the rear brakes	
<b>Standard Features</b>	<ul style="list-style-type: none"> <li>• Mechanically-controlled front and rear</li> <li>• Adjustable driving seat with suspension</li> <li>• Safety belts</li> <li>• Adjustable rear tow hook</li> <li>• Front tow hook</li> <li>• Folding roll bar</li> <li>• Adjustable wheel discs</li> <li>• Horn</li> <li>• Lights and direction indicators</li> <li>• 3- and 7-pole electrical outlet sockets rear</li> <li>• Central control panel</li> <li>• Safe start switch</li> <li>• Digital speedometer</li> <li>• Battery disconnect</li> <li>• Provision for flashing light attachment</li> </ul>	
<b>Optional</b>	<ul style="list-style-type: none"> <li>• Hydraulic lift with position and draft control</li> <li>• 540 and 1000 rpm PTO</li> <li>• Directable rear LED worklight</li> <li>• hydraulic system with single- and double-acting remote valves</li> <li>• Wheel ballasts</li> <li>• Tilt-adjustable steering column</li> <li>• Pneumatic seat suspension</li> </ul>	
<b>Dimensions</b>	with standard wheels: 7.50X16	

